



On the cover: Model R3431 SAN SSSL screener is designed to meet stringent USDA sanitary guidelines, particularly in dairy powder processing. Screener shown was installed in late 2015 at a dairy plant. Screener can handle up to 30,000 lb/h (13,600 kg/h) on certain dairy powders. Screener is capable of a single separation and provides more than 33 square feet (3 square meters) of screening area. Screener's typical applications require 30 mesh or larger screen openings. Courtesy of Rotex, Cincinnati, OH USA, +1 513 541 1236 (www.rotex.com).

POWDER and BULK ENGINEERING *International*

VOLUME 10, NUMBER 2

MARCH 2017

SCREENING AND CLASSIFYING

- 9 Screen deck maintenance for your gyrating sifter
Derek J. Williams
- 13 Equipment feature: Screening and classifying

FEEDERS

- 14 Three ways to improve continuous loss-in-weight feeding accuracy
Sharon Nowak
- 19 Equipment feature: Feeders

GENERAL FEATURES

- Cover 2 Ask an expert: Raw material changes affect alumina powder production
James L. Davis
- 7 Dust doctor: Requiring shop drawings for new dust collection systems
John A. Constance
- 20 Featured trade shows: CPhI Japan (Tokyo, 19-21 April), IDMA 2017 Fair (Istanbul, 4-7 May), Solids Dortmund (Dortmund, 10-11 May), SAMPE China 2017 (Beijing, 10-12 May), FCE Pharma (São Paulo, 23-25 May).

DEPARTMENTS

- | | |
|---------------------------|--------------------------|
| 4 Industry news | 23 Supplier notes |
| 8 Special section: Valves | Cover 3 Advertiser index |
| 22 Events | Cover 3 Product update |
| 23 Call for papers | |

www.pbeinternational.com

Powder and Bulk Engineering International [ISSN 1098-6480] (print) [ISSN 1944-8023] (online) is published six times a year in January, March, May, July, September, and November by CSC Publishing, Inc., 1155 Northland Drive, St. Paul, MN 55120 USA.